







# PrimeTrex IP

## Powerful Performer



-  Remote IP download capability
-  Multi-application capable
-  Flexible and user-friendly
-  64MB Flash and 32MB RAM
-  32-Bit ARM9 Processor
-  SD Card Reader for fast downloads

**Quick, reliable and affordable...**

**...PrimeTrex IP is your ideal desktop solution**

Depend on the reliability of **PrimeTrex IP**, while enjoying the flexibility of dial or Ethernet connectivity in one unit; all of the hardware is onboard. Fast and secure IP transactions, coupled with our 22 line per second printer, makes **PrimeTrex IP** the clear choice for speed. The 32-bit processor and abundant memory of **PrimeTrex IP** allow for quick access to a multitude of value-added applications. The three serial ports connect you to the peripheral devices needed to support them. Convenient, lightning-fast, and secure core application loads take only 10 seconds using the SD card reader.



## Specifications

Processor	32-bit ARM9 Processor
Memory	64MB Flash and 32MB RAM
Real Time Clock (RTC)	RTC has power backup for data retention while the external power is turned off
Magnetic Stripe Card Reader (MSR)	ISO MSR will read Tracks 1-2 with option of track 3
Smart Card Reader	Integrated
Display	Graphical LCD with 128 x 64 resolution
Keypad	Software programmable Integrated LED backlight
Speaker	Integrated multi-tone speaker
Full Graphic Thermal Printer	Clamshell design Number of dots per line: 384 Dots Printing width: 48 mm Paper width: 58 mm Paper diameter: 2.25 inch Printing speed: 22+ lines per second
Communication Options	3 RS232 (optional GPRS - 2 RS232) 1 RJ45 Ethernet Port 1 Dial Port <b>Wired dial modem 14,400bps</b> - V.31, V.22, V.22bis, V.23, V.29, V.32bis, Bell 103 and Bell 212 Supports both Synchronous and Asynchronous
Power	AC/DC power adapter, external, 100-240V
Environmental Specifications	•Operating Temperature 0°C to 40°C •Operating Humidity 10% to 90% non-condensing
Hardware Warranty	1 year
Size (L x W x H)	244mm x 138mm x 82mm



### Bottom of PrimeTrex IP



- 1 Dial Port
- 2 3 peripheral ports (Serial - RS232)
- 3 Ethernet/AUX
- 4 Power

### SD Card Reader

