



Speed, Security, Stability

PrimeTrex-S is your ideal desktop POS solution in an evolving industry with strict EMV timelines. Security, speed, reliable processing, and a focus on profit for you and your merchants make this terminal the best choice for a desktop solution today.

● Speed

With its 32-bit, ARM9 processor and 22 line-per-second printer, PrimeTrex-S provides your merchants with optimal transaction speeds. This desktop terminal also features an SD card reader for enhanced deployment with 10 second application downloads.

● Security

Security is at the highest level with PrimeTrex-S as it incorporates the latest in tamper protection and transaction encryption. The PCI 2.x, EMV Level 1 & 2 and PA-DSS certification gives PrimeTrex-S the security your merchants need for today and beyond.

● Stability

PrimeTrex-S is designed to provide a flexible and solid platform for today's complex applications, giving your merchants the reliability they need to effectively run their businesses.





PrimeTrex-S



Specifications

Processor:	32-bit ARM9 processor
Memory:	64M Flash, 32M RAM
Real Time Clock (RTC):	RTC has power back up for data retention while the external power is turned off
Magnetic Stripe Card Reader(MSR):	ISO MSR will read Track 1,2, 3 JIS MSR is bi-directional and will read track 1
Smart Card Reader:	Applicable
SD Card Reader:	Applicable
Full Graphic ThermalPrinter:	<ul style="list-style-type: none"> • Clamshell design • Number of dots per line: 384 Dots • Printing width: 1.8 inch • Paper width: 2.3 inch • Paper diameter: 2.25 inch • Printing speed: 22 lines per second
Display:	Graphical LCD with 128x64 resolution
Keypad:	Software programmable, backlit rubber keypad
Speaker:	Integrated, single-tone speaker
Communication Options:	<ul style="list-style-type: none"> • 3 RS232 (optional GPRS – 2 RS232) • 1 RJ45 Ethernet Port • 1 Dial Port • Wired dial modem 14,400bps - V.21, V.22, V.22bis, V.23, V.29, V.32bis, Bell 103 and Bell 212.
Power :	AC/DC power adapter, external, 100-240V
Environmental:	Operating Temperature: 0 C-40 C
Specifications:	Operating Humidity: 10% to 90% non-condensing
Hardware Warranty:	1Year
Dimensions:	225.2mm X 97.0mm X 55.0mm
Weight:	530g
Certifications:	<ul style="list-style-type: none"> PA-DSS PCI 2.x EMV Level I EMV Level II FCC part 15 FCC part 68 Industry Canada